



特点

焊脚采用2.54mm方阵排列
 触片设计特殊,具有优良的抗振动及冲击能力
 易清洁且通风性好
 极性分明,容易安装

电气特性

额定电流: 1 A
 接触电阻: 20 m
 绝缘电阻: 5000 M
 耐电压: 600 V r.m.s

机械特性

适用环境: - 55 ~ + 125

1150 - XXX - 0X - X

塑胶材料及颜色
 (Insulator material and color)
 4 : 棕色(Blown) PPS UL94V-0

镀层代码 (Plating code)

代码 (Code)	定义 (Definition)
1	Gold flash
2	5 μ m Sn Pb

引脚数量 (Pin number)
 020, 028, 032, 044, 052, 068, 084

规格	尺寸	A	B	C	D	E	F
28PIN		17.92	7.62	12.70	7.62	11.80	16.30
		17.92	7.62	12.70	7.62	11.80	16.30
32PIN		20.52	10.16	15.24	10.16	14.35	18.92
		23.42	12.70	17.78	12.70	17.20	21.80
44PIN		25.80	15.24	20.32	15.24	19.50	24.10
52PIN		31.00	20.32	25.40	20.32	24.70	29.35
68PIN		26.00	25.40	30.48	25.40	29.68	34.30

Features

Solder tails are positioned on 2.54mm square grid.
 Special contact is designed for high reliability and good withstanding to vibration and shock.
 Stand-off for cleaning and heat dissipation.
 Visual polarization for easy assembly.

Electrical

Current rating: 1A
 Contact resistance: 20m
 Insulation resistance: 5000 M
 Withstanding voltage: 600V r.m.s

Mechanical

Operating temperature: - 55 ~ +125

