




RSB-1102-11-A



RSB-1102-11-B



RSB-1102-11-C



RSB-1102-11-D

5	CONTACT	BRASS	1	Ag PLATED	6	BALL	STEEL	1	
3	TERMINAL	BRASS	2	Ag PLATED	4	SPRING	STEEL WIRE	1	
1	FRAME	NYLON	1		2	KNOB	NYLON	1	
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED

SPECIFICATION

TITLE: ROCKER SWITCH (1P1T)



RATING: AC 125V 3A / AC 250V 1.5A

CONTACT RESISTANCE: <math>< 30m\Omega</math> (1KHz, 10mA)

INSULATION RESISTANCE: >500M Ω (DC 500V)

WITHSTAND VOLTAGE: 1000V AC for 1min.

OPERATION FORCE: REFER ATTACH SPECIFICATION

SWITCHING LIFE: 10K cycles min.

MODEL NO: RSB-1102-11-()

TOLERANCE UNIT: MM

UP TO 1.0: ± 0.1 SCALE: 2:1

1.0 TO 10.0: ± 0.2 VERSION: 01

OVER 10.0: ± 0.3 DRWG NO:

DWN. *hoo*

CHK'D. *hoo*

APPD. *hoo*