



RECOMMEND P.C.B LAYOUT

NOTES:

1. MATERIALS
 - 1.1 Insulator:PC
 - 1.2 Contact:Brass, 0.3T
2. SPECIFICATIONS
 - 2.1 Current Rating: 3Amp
 - 2.2 Dielectric Strength:1000V AC for one minute
 - 2.3 Insulator Resistance:5000 M ohms Min
 - 2.4 contact Resistance:30m ohms Max
 - 2.5 Operation temperature:-55°C to +105°C
 - 2.6 INSERTION FORCE:<5kg
 - 2.7 EXTRACTION FORCE:>1.5kg

PART NO.	COLOR
ASC+0820-40C6	BLUE
ASC+0820-40C0	BLACK

DIMENSIONS TOLERANCE		METRIC	
0 = ±.3		設計 (DE' N)	
.00 = ±.2		審核 (CH' K)	
.0000 = ±.XXX		核准 (APP' D)	
ANG. = ±2'		繪圖 (DRAW)	
		單位 (UNITS)	mm
		數量 (QTY)	N/A
		材料 (M'T'L)	SEE NOTE
		處理 (FINISH)	SEE NOTE
		圖名 (NAME)	180度母方耳鍍錫鉚合蓋
		料號 (PART NUMBER)	ASC+0820-40C6
		圖號 (DRAW NUMBER)	RASC082040C6
		圖檔 (FILE NAME .DWG)	E:GCT/A/SC/08
		比例 (SCALE)	1/1
		圖紙 (SHEET)	A4
		頁次 (SHEET)	1
		版本 (REV.)	A

REV.	NOTES	DATE
A	RELEASED	2003/11/24