

# Pin connectors 2.54mm

Connecting Pin Ø0.47mm

Single row/double row

Solder tail

Series: PHB

## Right angle Pin connectors, Solder tail

### Technical Specs:

Insulator:	Black glass filled polyester PPS-GF30-FR
Flammability:	UL 94V-O
Sleeve:	Brass CuZn 36pb3(36000)
Mating pin Ø:	0.47 mm
Mechanical life:	min 500 cycles
Rated current:	3 A
Contact resistance:	max 10 mΩ
Dielectric strength:	min 1000V <sub>RMS</sub>



## Ordering information



PHB - NNN X - A P 1275A

No. of Positions	Insulator Type code	Pin Plating code
	1 Single row	1 Tin150μ"
	2 Double row	2 Tin200μ"
		3 GF
		4 Gold2μ"
		5 Gold3μ"
		6 Gold10μ"
		7 Gold15μ"
		S Special

PHB-NNN1-AP1275A

Right angle pin connector: solder tail, single row

Availability from: 2 to 40 contacts  
Standard number of contacts 20, 25, 32 and 40



PHA-NNN2-BP1275A

Right angle pin connector: solder tail double row

Availability from: 4 to 80 contacts  
Standard number of contacts 20, 40, 56, 60 and 72

